



DX 1000HT

1-TONNE, HI-TIP DUMPER

The DX 1000HT is the new No.1 Best in Class 1-tonne, high-tip dumper.

Designed to be owned by a rental company or professional operator. The DX 1000HT sets new standards for safety, strength, operator comfort and convenience and productivity on site.

With a proven, reliable Yanmar 3TNV76, 3 cylinder, Diesel engine....perfect for this application!



dX 1000ht 1-tonne hi-tip dumper

A DIAMOND IN THE ROUGH!!

FEATURES & BENEFITS

Operator Comfort and Convenience

• Fuel level is visible while in the operator's seat, saving time & improving safety & down time.

Increased leg room for improved operator comfort.

USB phone charger point, allowing charging while the work is done.

 Leading brand, comfort seat compliant to latest standards EN ISO 7096 for this type of equipment. Reduces operator fatigue, improves operator experience.

Strength

 Robust, easy-clean skip with fully returned edges preventing dirt ingress / concrete accumulation, reducing down time and cleaning costs.

• Strengthened chassis rails to increase durability.

 High quality, shot-blast and 2-layer powder coated paint finish for the most demanding site conditions.
Maximising resale values.

 Bushed & greased steering pivot cylinder, preventing wear on the main components, cost efficient for the owners.

Steel belly pan protector prevents damage to hydraulic circuit.

Front enclosure / infill plate reduces stone / mud ingress meaning less down time & cleaning required.

Steering Ram - Hose guard cover plate to prevent damage.

 Hi-quality leading brand all-terrain tyres fitted with valve protect guard, to reduce down time on site and increase productivity.



HIGH-QUALITY, ALL-TERRAIN TYRES WITH VALVE PROTECT GUARD & WHEEL NUT INDICATORS



ROBUST, EASY-CLEAN 1000KG CAPACITY SKIP FULLY RETURNED EDGES TO PREVENT DIRT INGRESS

Productivity

 The Altrad full 4 wheel drive system hydraulic system gives increased traction on poor terrain and excessive mud. Better gradeability, increased productivity and less servicing.

Reliable, Yanmar 3TNV76, water-cooled Diesel engine
perfect for this application.

 Market leading fuel tank capacity, reduces amount of fill-ups and down time.

 Unique fuel level indicator window together with a low fuel level warning light allows for easy inspection and assist in ensuring rental & machine productivity high.

- Low hydraulic fluid level warning light reducing system damage and down time.
- Extensive use of hose clamp retainers to prevent pipe fretting and rubbing, reducing hose failures and maintenance costs.
- Fuel and Hydraulic tank drain points reducing tank flushing time in the event of contamination or servicing.
- Fuel water separator reducing engine damage and down time.
- Central Hydraulic hoses enables increased protection, reducing the risk of down time.
- Under footplate stone guards preventing stone/mud ingress, so less down time & cleaning required.


esel engine

Safety

- Emergency Stop Button for increased safety.
- Tight turning circle allows better manoeuvrability on tight work sites, reducing shunting and increasing safety, productivity & efficiency.
- High viz access points & anti-slip foot-steps reduces slips, trips and falls when climbing on and off machine. Easily replaceable in case of an impact.
- Auto retracting seat belt prevents entanglement. Bright Orange for safety with increased visibility.
- Safe heavy duty, easy to deploy steering lock out bar, makes workshop and transport actives safer.
- "Check Point" visual wheel nut indicators make daily checks simpler to perform, reducing machine down time.
- Enclosed document box to retain machine safety documents reducing possibility of being damaged / misplaced.
- Lockable seat pan gas strut c/w lock out reduces chance of head / trapping injuries.
- Anti-slip, hot-dipped galvanised floor plate for safety and long life.
- Hazard warning chevron's on rear of dumper for increased machine visibility on site to others.
- Priority / safety steering valve that gives priority to the steer function in the event of low hydraulic fluid pressure or flow, therefore maintain-highest levels of machine safety at all times.



ROBUST STEEL, FRONT MATERIAL INGRESS GUARD PREVENTS DAMAGE TO HYDRAULIC CIRCUIT



system gives increased traction on poor

terrain and excessive mud. Better gradeability,

increased productivity and less servicing.

High viz access points reduces slips, trips and and off r Easily replaceable in

OPTION READY

Green Beacon, 2 x Worklights & 4 x Worklights options are available. Fully-loaded chassis harness and option-ready console means the options can be plugged-in and used immediately.

COMFORT SEAT & OPERATOR STATION

Leading brand, comfort seat compliant to latest standards EN ISO 7096 for this type of equipment. Reduces operator fatigue, improves operator experience.

Operator station gives increased leg room for improved operator comfort.

DX1000 HT

FOLDING ROPS

Robust folding ROPS as standard for the highest safety and easy transportation.

LOCKABLE SEAT PAN & GOOD SERVICE ACCESS

Lockable seat pan with locking gas strut reduces chance of head / trapping injuries. Gives good access to key service points for ease of servicing.

YANMAR 3TNV76 DIESEL ENGINE

Reliable, Yanmar 3TNV76, water-cooled Diesel engine - perfect for this application and Market leading fuel tank capacity, reduces amount of fill-ups and down time

SS POINTS

& anti-slip foot-steps falls when climbing on machine.

n case of an impact.

HIGH QUALITY TYRES & WHEEL NUT INDICATORS

High quality, leading brand all-terrain tyres for excellent off-road performance with "Check Point" visual wheel nut indicators make daily checks simpler to perform, reducing machine down time.

DX 1000HT 1-TONNE HI-TIP DUMPER | TRANSMISSION / DRIVE

Part Number

PERFORMANCE

Payload	(kg)1000
Unladen Weight	(kg)1363
Tipping Type	Front Tip - High
Turning Circle of Skip	(mm)2637
Turning Circle of Tyres	(mm)2524
Steering Angle	(°)39.7
Body Oscillation Angle	(°)15

CAPACITIES

Skip - Water	(Ltr)280
Skip - Struck	(Ltr)400
Skip - Heaped	(Ltr)500
Fuel Tank	(Ltr)35
Hydraulic Oil Tank	(Ltr)18

ENGINE

Engine Model	Yanmar 3TNV76
Туре	Diesel
No. of Cylinders	3
Gross Power	(Hp/kW)21.4 / 15.9
Displacement cc	(cc)1116
Max. Torque	(Nm)66.4

HYDRAULIC SYSTEM

Pump Type	Gear Pump
Flow Rate	(I/min)30
Operating Pressure	(bar/PSI)140
Steering Sytem	Hydraulic

BRAKING SYSTEM

Working Brake	Hydrostatic Dynamic Breaking
Parking Brake	Failsafe Automatic



GOOD ACCESS TO KEY FEATURES WITH SELF-LOCKING GAS STRUT AND PROVEN YANMAR 3TNY76 DIESEL ENGINE

Transmission Type	Hydrostatic Pump to 4 radial	
	piston Hydraulic Motors	
Tyre Size	255 / 75 -15.3	
Drive	Hydrostatic	
Max. Travel Speed	(kph)12	
(Unladen)		
Max. Gradient	25% (4:1)	

ENVIRONMENTAL

- Sound Pressure	(LpAd)84
Sound Power Level	(LWAd)101
Noise Emission (to ISO 4871)	

ELECTRICAL SYSTEM

System Voltage	(V)12
Battery Capacity	(Ah)44
Alternator Output	(A) 40


STANDARD EOUIPMENT

	_
Folding ROPS Frame	✓
Reversing Alarm	\checkmark
Flashing Orange Beacon	\checkmark
Hourmeter	\checkmark
Seat Belt (Hi-Viz Orange)	\checkmark
Adjustable Seat	\checkmark
Heavy Duty Articulation Lock	\checkmark
Wide Tyres	✓



ERGOMONIC OPERATOR STATION WITH EASY-TO-REACH CONTROLS, LEADING BRAND COMFORT SEAT AND GOOD ALL-ROUND VISIBILITY

STATIC DIMENSIONS*



		Standard Wheels	cw Wheel Spacers
A ¹ - Overall Length	(mm)	3165	3165
A ² - Overall Length (ROPS folded)	(mm)	3330	3330
B - Wheel base	(mm)	1440	1440
C - Minimum ground clearance	(mm)	250	250
D - Track width	(mm)	850	950
E - Width over tyres	(mm)	1100	1200
F - Height to top of ROPS (raised, with/without beacons)	(mm)	2545 / 2800	2545 / 2800
G - Height to top of ROPS (folded)	(mm)	1630	1630
H - Dump Height (untipped/tipped)	(mm)	1820 / 2960	1820 / 2960
J - Height to front lip of dumper body (untipped, lowered/raised)	(mm)	1110 / 2270	1110 / 2270
K - Height to front lip of dumper body (tipped, lowered/raised)	(mm)	400 / 1540	400 / 1540
L - Discharge distance front (lowered/raised)	(mm)	520 / 380	520 / 380
M - Dumper body tip angle	(°)	81	81
N - Departure angle	(°)	38	38

OPTIONS

Option Ready

- Green Beacon ready fitted with seat belt sensor & main harness is ready to take Green Beacon option.
- Twin Beacon and work light approved ROPS structure.
- Fully loaded chassis harness ready for options to be plugged in and used.
- Option ready console ready for options to be plugged in and used.
- Customer colour options giving excellent brand awareness.

Options Available

•	Work Lights x 2	OPD/20/DIO
•	Work Lights x 4	OPD/21/DIO
•	Green Beacon	OPD/22/DIO
•	Tow Hitch	OPD/24/DIO
•	UK Road Kit	OPD/25/DIO
•	50mm Wheel Spacers x 4	OPD/28/DIO
•	White Noise Back-Up Alarm	OPD/29/DIO
•	Site Anti-Tamper Kit	OPD/30/DIO

Worklights

- Available as a kit of 2 worklights or 4 worklights.
- Super bright 54W work light with 9 x 6W LED's, producing 4500 Lumens.
- Lightweight Aluminium Housing with stainless steel adjustable bracket.
- Protected to IP69K.
- Simple to fit / remove.

Green Beacon

- Tough, leading brand quality 9W beacon with 40 LED's.
- Simple to fit / remove.
- Lockable under-canopy storage for both the Green & Orange beacons.
- Flexible mounting to reduce damage.

LOCKABLE UNDER-CANOPY BEACON STORAGE



Tow Hitch

- Ideal for moving trailers, caravans etc. around site.
- 750kg maximum towing weight on flat ground (including the weight of the towed equipment).
- Combination hitch 50mm Ball & Jaw/Pin.
- Adjustable height for correct towing position.
- Simple to fit / remove.



TOW HITCH OPTION

OPTIONS

UK Road Kit

- Kit includes headlights, brake lights, front & rear facing indicators, number plate mount (c/w number plate light and the following console switches/displays:-
 - Side Lights Switch
 - Road Lights Switch
 - Indicators Switch
 - Hazard Lights Switch
 - Display Indicator
- Accepts 279mm x 203mm standard, rear facing number plate
- 60/55W Headlights are enclosed in a durable steel mesh cage and mounted on a robust bumper bar for added protection.
- Red, White & Amber reflectors for increased visibility in poor light conditions.
- Simple to fit / remove.
- Designed to comply with BS ISO 12509:2004

Wheel Spacers

- Increases the track width of the machine by 100mm giving added safety and stability in both static and dynamic conditions.
- Locking nuts for additional safety.
- Removeable for tight-access jobsites.
- Compatible with existing machines
- Corrosion resistant protective coating.
- Simple to fit / remove.



BRAKE LIGHTS, INDICATORS & NUMBER PLATE MOUNT FROM UK ROAD KIT OPTION



HEAD LIGHTS & INDICATORS FROM UK ROAD KIT OPTION



WHEEL SPACER OPTION ADDS 100MM TO THE TRACK WIDTH GIVING ADDED SAFETY & STABILITY



